



KNR-3200R(P)

Full HD Real-time 32CH NVR with PoE /NON-POE



FUNCTION

- ***Plug & Play** with **Built-in PoE** (Max. 16ch)
- ***ONVIF** Compatible & **Auto IP Camera Detection**
- *Various Connection Method depending on user/site
- *Max. **4K RESOLUTION** RECORDING
- *6HDD SUPPORTED
- *Remote Monitoring by Remote S/W(CMS) & Smart Phone



[KNR-3200RP (3200R)]

SPECIFICATOIN

Model Name		KNR-3200R (32ch - NON POE)	KNR-3200RP (16CH-POE)
Video	Input	32 IP	
	Input Resolution	32ch Max 4MP (24ch 5MP,16ch 4K)	
	Output	1 HDMI, 1 VGA, 2 BNC(1 HD, 1 SD)	
	Output Resolution	4K, FHD, SXGA, XGA	
Recording	Speed	7.5fps/ch (4MP) /15fps (2MP)	
	Resolution	32ch Max 4MP (24ch 5MP,16ch 4K)	
Audio	Input	Depends on IP, 1 RCA	
	Output	1 HDMI, 1 RCA	
Interface	Senser In / Out	4 /1 - NC / NO	
	USB	2 x USB 2.0	
	PTZ / Keyboard	2 x RS485 - Terminal Block	
Network	ATM /POS	Ethernet POS	
	Interface	2 x Ethernet 10/100/1G	
	Compression	H.265, JPEG	
	Speed	10fps (4MP), 20fps (2MP)	
System	Resolution	Max. 4MP	
	OS	Embedded Linux (Built-in Flash Memory)	
	Pre / Post-Alarm	5sec / 5sec~5min	
	Recording Mode	Continuous, Event, Schedule	
	Data Search	Smart, Panorama, Calendar, Multi Day / Time, Event, Go to Time	
	Backup Interface	USB, Network	
	Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data	
	Alarm Action	Buzzer, PTZ Preset, E-mail, Relay, Spot, Event Popup, Callback, FTP, Push	
	User	15 Users (Admin, User1 ~ User14)	
	Network Viewer	VMS, Web Viewer, Mac Viewer, SmartEyes_Pro(iOS, Androld)	
Storage	ONVIF	ONVIF Profile S	
	Primary / External	6 HDD, 4 eSATA	
General	Size	440 x 88 x 430 mm	
	Weight(w/o HDD)	8kg	
	Temp / Humidity	5 ~ 40 ℃ / 10% ~ 80%	
	PoE	N/A	16 PoE
	Power Supply	IEEE 802.3at, Max. 150W	
	Power Consumption	AC 100 ~ 250V, 50/60 Hz	
		230 Watts	

(*) Design and specification are subject to change without prior notice

